

Product Sheet

Product details	BK-MAXLINE-SX-391-0-1A
Pixel Pitch (mm)	5,91 (3,91 optional)
Physical Density (Pixel/m²)	65.536
LED Arrangement	1R1G1B
LED Type	SMD1921 (white)
Module Size (mm x mm)	250x250
Module resolution (Px x Px)	64x64
Drive mode	Constant Current Drive
Scanning Mode	1/12
Horizontal Viewing Angle (Deg.)	140
Vertical Viewing Angle (Deg.)	120
Brightness (cd/m²)	>5000
Grey Scale	14 - 16 Bit
Refresh Rate (Hz)	~ 3.840
High refresh rate IC driver	ICN – High Refresh
Max Power Consumption (W)	600 / sqm
Average Power Consumption (W)	~ 180 / sqm
Cabinet Size (mm x mm)	500x1000mm / 500x500mm
Cabinet Resolution	128 x 256 / 128 x 128
Cabinet Thickness (mm)	90
Weight (Kg)	~ 36kg / qm plus Kabel
Cabinet Material	Aluminium
Color (M)	>16.7
Serviceability	Front- & Back Service
Input Voltage (V)	AC 240V +/- 10% @ 50Hz
Protection Level	IP65
Working Temperature (°C)	-20°-+45°
Operation humidity (RH)	10%-85%
LED control system design	Novastar
Certificates	CE, ROHS, PFC, EMC Class A, LVD

Alle Daten vorbehaltlich Änderungen. Techn. Daten können ohne Vorankündigung geändert werden.